



Aquasol Controllers, Inc.

We Simply Control Pools Since 1975

OUTPUT

Item Number Prefix	Pump Tube	Roller Assembly	Gallons per Day	Gallons per Hour	Ounces per Hour	Ounces per Minute	Pressure psi	Liters per Day	Liters per Hour	Milliliters per Hour	Milliliters per Minute	Pressure bar
E10T1F*	F	White	0.6	0.02	3.0	0.05	80	2.2	0.09	90.0	1.50	5.5
E10T2F*	F	White	1.3	0.05	6.6	0.11	80	4.8	0.20	198.0	3.30	5.5
E20T4F*	F	White	3.4	0.14	18.0	0.30	80	13.1	0.54	544.8	9.08	5.5
E20T4G*	G	Black	12.3	0.51	65.4	1.09	80	46.5	1.94	1937.4	32.29	5.5
E20T4H*	H	Black	21.7	0.90	115.2	1.92	80	82.0	3.41	3416.4	56.94	5.5
E10T1A	A	White	2.5	0.10	13.2	0.22	25	9.5	0.39	396.0	6.60	1.7
E10T2A	A	White	5.0	0.21	26.4	0.44	25	18.9	0.79	786.0	13.10	1.7
E10T2B	B	White	8.5	0.35	45.6	0.76	25	32.2	1.34	1338.0	22.30	1.7
E10T2C	C	White	15.0	0.63	79.8	1.33	25	56.8	2.37	2364.0	39.40	1.7
Approximate Maximum Outputs @ 50/60Hz												

* Injection check valve included with pumps rated 80 psi (5.5 bar)



NOTICE: The information within this chart is solely intended for use as a guide. The output data is an approximation based on pumping water under a controlled testing environment. Many variables can affect the output of the pump. Stenner Pump Company recommends that all metering pumps undergo field calibration by means of analytical testing to confirm their outputs.